MULTI-BEAM SCANNING OPTICAL APPARATUS AND

IMAGE FORMING APPARATUS USING THE SAME

BACKGROUND OF THE INVENTION

5   Field of the Invention

The present invention relates to a multi-beam
scanning optical apparatus and image forming apparatus
using the same and, more particularly, to an image
forming apparatus such as a laser beam printer having,
10   e.g., an electrophotographic process, digital copying
machine, or multi-functional printer, in which a
plurality of light beams emitted from a light source
means having a plurality of light emitting portions are
deflected by a polygon mirror serving as an optical
15   deflector and then caused to be optically scanned on a
surface to be scanned through scanning optical means
having an f-θ characteristic so as to record image
information.

Related Background Art

20   A scanning optical apparatus (scanning optical
system) conventionally used for an image forming
apparatus is often designed to guide a light beam
emitted from light source means to deflection means
through an incident optical means and to form and scan
25   the spot image of the light beam deflected by the
deflection means on a surface to be scanned through
scanning optical means having an f-θ characteristic.

Along with the recent improvement in performance and multi-functional ability of image forming apparatuses, scanning optical apparatuses are also required to operate at a high speed. To meet this

5   requirement for high-speed operation, a plurality of light sources (light emitting portions) are used. In, e.g., Japanese Patent Application Laid-Open No. 9-54263, a multi-beam laser chip for emitting a plurality of linearly arranged light beams (laser

10   beams) from one chip is used as light source means.

In an image forming apparatus, generally, if the interval between scanning lines in the sub scanning direction changes depending on position due to various reasons, the printed image quality degrades.

15   Especially, this phenomenon readily takes place in a multi-beam scanning optical apparatus having a plurality of light emitting portions because of the presence of the plurality of light emitting portions.

20   SUMMARY OF THE INVENTION

It is an object of the present invention to provide a multi-beam scanning optical apparatus which reduces errors in interval between scanning lines in a sub-scanning direction within the effective scanning

25   region by setting elements such that the sub-scanning interval error between the scanning lines on the scanning surface, which is caused by a difference in

polarization angle between light beams emitted from a

plurality of light emitting portions, falls within a

predetermined value/level, thereby executing

high-quality printing at a relatively low cost, and an

5   image forming apparatus using the same.

According to one aspect of the invention, there is

provided a multi-beam scanning optical apparatus which

comprising:

incident optical means for making a plurality of

10   light beams emitted from light source means having a

plurality of light emitting portions incident on

deflection means; and

scanning optical means for forming images of the

plurality of light beams deflected by said deflection

15   means on a surface to be scanned,

wherein said scanning optical means has at least

one scanning optical element made of a resin, and said

scanning optical element made of the resin has

birefringence due to a stress distribution generated

20   upon cooling in a molding process thereof such that the

directions of principal axes of birefringence at one

end portion of said scanning optical element made of

the resin are different from those at the other end

portion, opposite to said one end portion with respect

25   to an optical axis thereof in a main scanning

direction, of said scanning optical element made of the

resin, and

wherein an interval between adjacent scanning
lines of scanning lines formed on the scanning surface
by the plurality of light beams whose images are formed
on the scanning surface through said scanning optical

5   element made of the resin changes in the main scanning
direction in an effective scanning region, and

wherein said apparatus comprises at least one
setting means for setting a sub-scanning interval error
between the scanning lines due to a polarization angle

10   difference between the light beams emitted from the
plurality of light emitting portions to be not more
than 1/5 of a desired scanning line interval.

In further aspect of the scanning optical
apparatus according to the invention, the direction of

15   the principal axes of the birefringence at the end
portions of said scanning optical element made of the
resin form an asymmetrical distribution due to the
stress distribution generated upon cooling in the
molding process of said scanning optical element made

20   of the resin.

In further aspect of the scanning optical
apparatus according to the invention, said apparatus
has a plurality of scanning optical elements made of
the resin.

25   In further aspect of the scanning optical
apparatus according to the invention, said scanning
optical means includes refractive optical elements all

- 5 -

of which are scanning optical elements made of a resin.

In further aspect of the scanning optical apparatus according to the invention, said scanning optical means includes a scanning optical element made of glass.

In further aspect of the scanning optical apparatus according to the invention, said scanning optical means includes a reflecting optical element having a power.

In further aspect of the scanning optical apparatus according to the invention, said setting means sets the polarization angle difference between the light beams emitted from the plurality of light emitting portions to be not more than 20°.

In further aspect of the scanning optical apparatus according to the invention, said setting means comprises correction means for correcting the polarization angle difference between the plurality of light beams incident on said scanning optical element made of the resin.

In further aspect of the scanning optical apparatus according to the invention, said correction means comprises polarized light limiting means inserted into an optical path between the light source means and said scanning optical element made of the resin.

In further aspect of the scanning optical apparatus according to the invention, said polarized

light limiting means is tilted with respect to the optical axis of said incident optical means.

In further aspect of the scanning optical apparatus according to the invention, the plurality of light emitting portions are independently arranged.

In further aspect of the scanning optical apparatus according to the invention, said setting means comprises adjustment means capable of independently adjusting polarization angles of the light beams emitted from the plurality of light emitting portions.

In further aspect of the scanning optical apparatus according to the invention, the light source means comprises a monolithic multi-beam light source.

In further aspect of the scanning optical apparatus according to the invention, said apparatus has a plurality of monolithic multi-beam light sources.

In further aspect of the scanning optical apparatus according to the invention, said setting means comprises adjustment means capable of independently adjusting polarization angles of the light beams emitted from the plurality of monolithic multi-beam light sources.

In further aspect of the scanning optical apparatus according to the invention, said setting means comprises a scanning optical element made of a resin, which is shift-decentered perpendicularly to a

sub scanning direction and/or rotary-decentered about the main scanning direction.

In further aspect of the scanning optical apparatus according to the invention, letting h be a sub-scanning width of said scanning optical element made of the resin and d be an optical-axis-direction width, $h/d \leq 1.8$ is satisfied.

In further aspect of the scanning optical apparatus according to the invention, letting h be a sub-scanning width of said scanning optical element made of the resin and t be a sub-scanning width of the light beam passing through said scanning optical element made of the resin, $h/t \leq 15$ is satisfied.

In further aspect of the invention, there is provided an image forming apparatus comprising:

said multi-beam scanning optical apparatus set out in the foregoing;

a photosensitive member disposed in the scanning surface;

a developer for developing, as a toner image, an electrostatic latent image formed on said photosensitive member by light beams scanned by said multi-beam scanning optical apparatus;

a transfer device for transferring the developed toner image onto a transfer member; and

a fixing device for fixing the transferred toner image on the transfer member.

In further aspect of the invention, there is
provided an image forming apparatus comprising:

said multi-beam scanning optical apparatus set out
in the foregoing; and

5   a printer controller for converting code data
received from an external device into an image signal
and inputting the image signal to said scanning optical
apparatus.

10   BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a sectional view showing the main part
in the main scanning direction in the first embodiment
of the present invention;

Fig. 2 is a view showing the layout of light

15   emitting portions in the first embodiment of the
present invention;

Fig. 3 is a sectional view showing the main part
in the main scanning direction in the second embodiment
of the present invention;

20   Fig. 4 is a sectional view showing the main part
in the main scanning direction in the third embodiment
of the present invention;

Fig. 5 is a view showing the arrangement of light
source means according to the third embodiment of the

25   present invention;

Fig. 6 is a view showing another arrangement of
the light source means according to the third

embodiment of the present invention;

Fig. 7 is a sectional view showing the main part in the main scanning direction in the fourth embodiment of the present invention;

5   Fig. 8 is a view showing the arrangement of light source means according to the fourth embodiment of the present invention;

Fig. 9 is a sectional view showing the main part in the main scanning direction in the fifth embodiment

10   of the present invention;

Fig. 10 is a view showing the positional relationship between light beams in the fifth embodiment of the present invention;

Fig. 11 is a view showing the positional

15   relationship between light beams and their image forming positions in the fifth embodiment of the present invention;

Fig. 12 is a view showing the positional relationship between scanning lines at the time of

20   decentration in the fifth embodiment of the present invention;

Fig. 13 is a sectional view showing the main part in the main scanning direction in the fifth embodiment of the present invention;

25   Fig. 14 is a sectional view showing the main part in the main scanning direction in the fifth embodiment of the present invention;

Fig. 15 is a sectional view showing the main part in the sub scanning direction of an image forming apparatus (electrophotographic printer) using a scanning optical apparatus of the present invention;

5   Fig. 16 is a view showing the relationship between a principal axis and a polarization direction P of an incident beam;

Fig. 17 is a front view of an optical element;

Fig. 18 is a view showing a principal axis

10   distribution at the central portion of a lens;

Figs. 19A and 19B are views showing principal axis distributions at lens end portions;

Figs. 20A and 20B are views showing polarization directions of an incident beam;

15   Fig. 21 is a view showing the ideal intensity distribution in a spot;

Fig. 22 is a view showing the intensity distribution in a spot of an end light beam;

Fig. 23 is a view showing the intensity

20   distribution in a spot when the polarization direction is tilted;

Fig. 24 is a view showing the transition of the intensity distribution in a spot when the polarization direction is tilted;

25   Fig. 25 is a view showing a tilt of a scanning line;

Figs. 26A, 26B, 26C, 26D and 26E are explanatory

views showing tilts of scanning lines when a single

light emitting portion or two light emitting portions

are present;

Fig. 27 is a view showing the phase distribution

5   between light beams;

Fig. 28 is a view showing the phase distribution

between light beams;

Fig. 29 is a view showing the polarization

direction of a portion of the light beam after passing

10   through a resin lens;

Figs. 30A, 30B and 30C are views each showing the

polarization direction of a portion of the light beam;

Figs. 31A and 31B are views each showing the

relationship between the polarization directions of the

15   incident and exit light beams and the principal axis;

Fig. 32 is a view showing the polarization

direction of a portion of the light beam after passing

through a resin lens.

Fig. 33 is an explanatory view showing the

20   relationship between the principal axes of

birefringence and a stress distribution generated in a

resin lens;

Figs. 34A and 34B are explanatory views showing

tilts of scanning lines when four light emitting

25   portions are present;

Fig. 35 is an explanatory view showing an example

using a single resin scanning lens of the present

invention; and

Fig. 36 is an explanatory view used for the sixth embodiment in which a single light emitting portion is present.

5

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In an image forming apparatus, generally, if the interval between scanning lines in the sub scanning direction changes depending on the position due to

10 various reasons, the printed image quality degrades. Especially, this phenomenon readily takes place in a multi-beam scanning optical apparatus having a plurality of light emitting portions because of the presence of the plurality of light emitting portions.

15 Causes for this phenomenon are:

(1) The optical surface (optical system) has not been so manufactured as to agree with design value.

(2) The magnification in the sub scanning direction (sub-scanning magnification) of the scanning

20 optical means is not constant with respect to the main scanning direction.

(3) A light beam is not perpendicularly incident on a photosensitive drum surface.

In addition, the interval between scanning lines

25 in the sub scanning direction also changes when light beams emitted from the plurality of light emitting portions have different polarization angles.

Many scanning optical apparatuses use an optical element (plastic lens) made of resin as a scanning optical means for the sake of cost and surface shape processing. Since an optical element made of a resin

5   generally tends to have birefringence, the refractive index of such optical element made of a resin changes depending on the polarization direction of the incident beam. When a light beam is incident on such an optical element, the light beam is split into two light beams

10   whose polarization directions are perpendicular to each other. The two light beams propagate through the lens and are synthesized after emerging from the lens. In this specification, the two polarization directions perpendicular to each other will be referred to as

15   principal axes.

Let P be the polarization direction of an incident beam when a light beam La (not shown) is incident on an optical element GA from a direction perpendicular to the sheet surface, as shown in Fig. 16, No and Ne be

20   the principal axes of birefringence of the optical element GA, and θ be the angle made by the polarization direction P of the incident beam La and the principal axis Ne of birefringence. In this case, the light beam is split into two polarized light components, i.e., a

25   polarized light component Po in the No direction and a polarized light component Pe in the Ne direction, in the optical element GA. The polarized light components

Po and Pe propagate in accordance with their refractive

indices. For this reason, a phase difference is

generated between the polarized light components, and

the linearly polarized light beam changes to

5   elliptically polarized light or the like.

The polarized light components Po and Pe are given

by Po = P·sinθ and Pe = P·cosθ, respectively. The

intensity of each of the polarized light components Po

and Pe is proportional to its square.

10   In a scanning optical apparatus, a light beam

deflected by deflection means passes through scanning

optical means (f-θ optical system) while moving in the

main scanning direction and changing its position.

Scanning optical means often uses, e.g., a molded

15   optical element for the purpose of cost reduction.

Such an optical element has birefringence that changes

depending on position due to a temperature distribution

and stress distribution which are generated in a mold

upon cooling, as will be described with reference to

20   Figs. 17, 18, 19A, and 19B.

Especially, molding using a resin material is

advantageous in terms of cost but readily causes

birefringence. In a lens which is molded by cooling

for a time as short as 5 min, the directions of

25   principal axes of birefringence largely change

depending on the position in the lens.

Fig. 33 is a plan view showing the optical element

(lens) GA used in scanning optical means, which is viewed from the direction of an optical axis OA. Fig. 33 shows the stress distribution in the lens. Internal stress acts in a direction perpendicular to

5   curves shown in Fig. 33. The principal axes of birefringence are directed in the horizontal and vertical directions with respect to the curves.

Fig. 17 is a plan view of the optical element (lens) GA used in the scanning optical means when

10   viewed from the direction of the optical axis OA. Referring to Fig. 17, a light beam 30 passes through a region at the central portion of the lens, a light beam 31 passes through a region at one lens end portion, and a light beam 32 passes through a region at the other

15   lens end portion. Figs. 18, 19A and 19B are views showing the directions of principal axes of birefringence of the optical element in the light beams 30, 31, and 32 on an optical element 6A shown in Fig. 17, respectively.

20   As shown in Figs. 18, 19A, and 19B, the directions of principal axes of birefringence change depending on position in the lens. This is because the directions of the principal axes of birefringence are affected by the temperature distribution that is generated upon

25   cooling during molding. For example, the directions of principal axes in the section of the light beam 30 passing through the central portion of the lens almost

match the long axis (main scanning direction) and short

axis (sub scanning direction) of the lens because of

the symmetry in the vertical and horizontal direction

of the lens, as shown in Fig. 18. At this time, if the

5   polarization direction of the incident beam La which is

incident on the optical element GA matches a long axis

Y or short axis Z, as shown in Fig. 20A, the angle made

by the polarization direction P of the incident beam

and the principal axis is almost 0° or 90° , and

10   polarized light components in different directions are

hardly generated in the lens. Hence, a spot on the

scanning surface obtained at this time has an almost

ideal intensity distribution indicated by a curve 36 in

Fig. 21. Referring to Fig. 21, the abscissa represents

15   the sub scanning direction, and the ordinate represents

the intensity distribution of a formed spot. This

relationship between the ordinate and the abscissa also

applies to Figs. 22, 23, and 24 to be described later.

To the contrary, for example, when the

20   polarization direction P of the incident beam La

passing through the central portion of the lens is

tilted with respect to the long axis Y or short axis Z,

as shown in Fig. 20B, a polarized light component in a

different direction is generated in accordance with the

25   tilt. In this case, since the angle θ made by the

polarization direction P and principal axis rarely

changes in the entire region of the light beam, an

almost uniform phase difference is generated in the

light beam. Hence, a finally obtained spot has an

almost ideal intensity distribution like the curve 36

shown in Fig. 21, as in the case wherein the

5   polarization direction P of the incident beam matches

the long axis or short axis of the lens.

However, the tilts of principal axes in the

section of the light beam 31 that passes through the

lens end portion have a distribution asymmetric in the

10   vertical direction, as shown in Fig. 19A. In this

case, the tilts of the principal axes change depending

on position within the light beam, and the tilts of the

principal axes become larger away from the central

portion toward the end portion of the lens. As a

15   result, even when the incident beam La that becomes

incident on the optical element GA has the polarization

direction P in the direction of the long axis Y or

short axis Z of the lens, as shown in Fig. 20A, a

polarized light component different from that of the

20   incident beam appears in the light beam propagating

through the lens, and the amount of the polarized light

component changes depending on position in the light

beam. Fig. 29 shows the polarized state of the light

beam after passing through the lens end portion.

25   Referring to Fig. 29, three sets of arrows

perpendicular to each other indicate principal axes, as

in Figs. 19A and 19B, and two ellipses on the upper and

lower sides and the horizontal line at the center

indicate the polarized states of the light beam after

passing through the lens. Arrows on the ellipses

indicates the rotation directions of polarized light.

5   Referring to Fig. 29, the light component transmitted

through the central portion emerges in the same

polarized state as that of the incident beam because

the polarization direction of the incident beam matches

the direction of the principal axis. On the other

10   hand, the light components transmitted through the

upper and lower portions are converted from linearly

polarized light to elliptically polarized light, as

shown in Fig. 29, because the polarization direction of

the incident beam does not match the direction of the

15   principal axis.

The polarized light components exhibit rotation

directions as shown in Fig. 29. This will be described

below in detail.

Figs. 31A and 31B are views showing the

20   relationship between the polarization direction of an

incident beam, principal axes, and the polarization

direction of an exit beam. Fig. 31A shows a light

component at the upper portion of the light beam, and

Fig. 31B shows a light component at the lower portion

25   of the light beam. The light beam that becomes

incident on the lens is split into two light beams in

accordance with the directions of principal axes.

- 19 -

Referring to Figs. 31A and 31B, the light beam is split
into light beams having polarized light components in
the Ne and Ne directions. As the split light beams
pass through a lens having birefringence, the phase of

5   the polarized light component in the Ne direction
shifts from that of the polarized light component in
the No direction. Consequently, the light beam
synthesized after emerging from the lens is converted
from linearly polarized light to elliptically polarized

10   light. Assuming that the phase of the polarized light
component in the Ne direction is delayed from that in
the No direction by $\pi/4$, elliptically polarized light
having a rotation direction as shown in Fig. 31A or 31B
is obtained.

15   At this time, since the directions of tilt of
principal axes are reversed with respect to the center,
the rotation direction of polarized light is also
reversed with respect to the center.

         The rotation and vibration of each polarized light

20   component in the light beam are not disorderly. When
the polarized light component at the upper portion of
the light beam indicates direction (1) in Fig. 32, each
of the polarized light components at the center and
lower portion of the light beam indicates its direction

25   (1). When the polarized light component at the upper
portion indicates directions (2), (3), and (4) in Fig.
32, each of the polarized light components at the

center and lower portion of the light beam indicates

its directions (2), (3), and (4), respectively. For a

polarization distribution in such a light beam at an

arbitrary timing, the polarized light component in the

5   horizontal direction in Fig. 29, which matches the

polarization direction of the incident beam, is

directed to the same direction independently of the

position in the light beam. On the other hand, the

components on the upper and lower sides in Fig. 29,

10 which are perpendicular to the polarization direction

of the incident beam, are directed in opposite

directions with respect to the central portion.

Figs. 30A to 30C are views showing the

polarization directions of emerging beams at the

15 respective positions at timing (2) in Fig. 29.

The set of arrows in Fig. 30A indicates the

polarization direction at the upper portion of the

emerging beam, and its horizontal and vertical

components with respect to the polarization direction

20 of the incident beam. The sets of arrows in Figs. 30B

and 30C indicate the polarization directions at the

respective positions in the exit beam, and its

horizontal and vertical components with respect to the

polarization directions of the incident beam.

25 As described above, all components in the

direction (horizontal direction) parallel to the

polarization direction of the incident beam are

directed in the same direction, while components in the direction (vertical direction) perpendicular to the polarization direction of the incident beam are directed in opposite directions with respect to the central portion, as shown in Fig. 30A and Fig. 30C.

When such a state of components perpendicular to the polarization direction of the incident beam is expressed by the form of a phase difference distribution, the light beam has a phase difference distribution as shown in Fig. 27. Referring to Fig. 27, the abscissa represents the vertical direction (Z direction) of the lens GA, and the ordinate represents the phase difference of polarized light perpendicular to the polarization direction of the incident beam with respect to the phase at the center of the light beam 31.

A light beam whose components are in phase forms one spot image, but a light beam whose components have inverted phases forms a plurality of spot images, as is known. As described above, the phase of a component perpendicular to the polarization direction of the incident beam passing through a lens end portion is inverted with respect to the center in the sub scanning direction. As a result, a polarized light component perpendicular to the polarization direction P of the incident beam forms a spot image having an intensity distribution with two peaks indicated by a curve 38c in

- 22 -

Fig. 22 on the scanning surface. On the other hand,
since a polarized light component parallel to the
polarization direction P of the incident beam has a
uniform phase in the light beam, the spot formed on the

5   scanning surface is a normal spot having an intensity
distribution indicated by a curve 38b in Fig. 22. The
two polarized light components are perpendicular to
each other and therefore do not interfere with each
other. Hence, a finally obtained spot is an enlarged

10   spot indicated by a curve 38a obtained by superposing
the two curves 38b and 38c shown in Fig. 22.

When the polarization direction P of the incident
beam La is tilted with respect to the long axis Y or
short axis Z of the optical element GA, as shown in

15   Fig. 20B, the polarization direction P of the incident
beam does not match the direction of the principal axis
even at the center of the light beam La. For this
reason, the light beam has a phase difference
distribution shown in Fig. 28. Referring to Fig. 28,

20   the abscissa represents the vertical direction (Z
direction) of the lens GA, and the ordinate represents
the phase difference of polarized light perpendicular
to the polarization direction of the incident beam.

Referring to Fig. 28, the phase difference is

25   inverted at a position separated from the center,
unlike Fig. 27. This is because the polarization
direction P of the incident beam is tilted as mentioned

above, and therefore, the polarization direction P of
the light beam matches the direction of the principal
axis at the position separated from the center.
Because of the influence of deviation of phase
5   inversion position from the center, the polarized light
component perpendicular to the polarization direction P
of the incident beam forms, on the scanning surface, a
spot having an intensity distribution with two peaks
deviated from the center, as indicated by a curve 39c
10   in Fig. 23.

On the other hand, a component parallel to the
polarization direction P of the incident beam has a
uniform phase in the light beam, as before the incident
beam is tilted, and therefore forms, on the scanning
15   surface, a normal spot having an intensity distribution
indicated by a curve 39b in Fig. 23. The two polarized
light components are perpendicular to each other and
therefore do not interfere with each other. Hence, a
finally obtained spot is an enlarged spot deviated to
20   the left side (the lower side of the lens), as
indicated by a curve 39a obtained by superposing the
two curves 39b and 39c shown in Fig. 23.

At the other end, since the principal axes have
tilts reverse to those in Fig. 19A, as shown in
25   Fig. 19B, the spot finally obtained on the scanning
surface is an enlarged spot deviated to the right side
(the upper side of the lens), unlike the curve 39a

shown in Fig. 23.

If the polarization direction P of the incident beam does not match the long axis or short axis of the lens, the peak position of the intensity distribution

5   of a spot on the scanning surface moves, as shown in Fig. 24, as the light beam changes its transmission position on the lens, and a scanning line finally obtained on the scanning surface is tilted, as shown in Fig. 25.

10   When only one light emitting portion is present, all scanning lines on a scanning surface SP are tilted in the same way in the effective scanning region, as shown in Fig. 26A. For this reason, the influence on the printing quality is relatively small. However,

15   when a plurality of light emitting portions are present, and they have no uniform polarization direction P, scanning lines on the scanning surface SP are tilted in various ways in the effective scanning region, as shown in Figs. 26B to 26E, resulting in

20   degradation in printing quality.

Figs. 26B to 26E show examples with two light emitting portions in a scanning optical apparatus. A scanning line formed by a light beam emitted from one light emitting portion A is defined as line A, and a

25   scanning line formed by a light beam emitted from the other light emitting portion B is defined as line B. The tilts of scanning lines on the scanning surface are

shown in correspondence with the polarization

directions P of the light emitting portions A and B.

Referring to Figs. 26B to 26E, the interval

between the adjacent scanning lines A and B of the

5   scanning lines formed on the scanning surface changes

in the main scanning direction in the effective

scanning region. The sub-scanning interval between the

adjacent scanning lines A and B at the left end is

different from that at the right end, resulting in

10   degradation in printing quality. Referring to

Figs. 26B and 26E, the sub-scanning interval between

the adjacent scanning lines A and B monotonically

increases in the sub scanning direction from the left

to the right. Conversely, referring to Figs. 26C and

15   26D, the interval monotonically decreases.

Figs. 34A and 34B show examples using four light

emitting portions in a scanning optical apparatus. The

light emitting portions are sequentially arranged in

one direction, for which a scanning line formed by a

20   light beam emitted from a first light emitting portion

A is defined as line A, a scanning line formed by a

light beam emitted from a second light emitting portion

B is defined as line B, a scanning line formed by a

light beam emitted from a third light emitting portion

25   C is defined as line C, and a scanning line formed by a

light beam emitted from a fourth light emitting portion

D is defined as line D. The tilts of scanning lines on

the scanning surface are shown in correspondence with the polarization directions P of the light emitting portions A, B, C, and D.

In the above-description, the light emitting portions have almost the same polarization direction. The above-described scanning line interval error still occurs when the polarization directions of light emitting portions are almost perpendicular to each other.

Fig. 32 shows the polarized state of the light beam 31 shown in Fig. 17 after passing through the lens, as in Fig. 29. Fig. 32 is different from Fig. 29 in that the polarization direction of an incident beam is directed in the vertical direction in Fig. 32. The meanings of arrows are the same as in Fig. 29.

Referring to Fig. 32, the light component transmitted through the central portion emerges in the same polarized state as that of the incident beam because the polarization direction of the incident beam matches the direction of the principal axis. On the other hand, the light components transmitted through the upper and lower portions are converted from linearly polarized light to elliptically polarized light, as shown in Fig. 32, because the polarization direction of the incident beam in the respective portions does not match the direction of the principal axis.

As shown in Fig. 32, the directions of polarized
light components parallel to the polarization direction
of the incident beam always match independently of the
position in the light beam. However, components
5   perpendicular to the polarization direction of the
incident beam are always directed in opposite
directions at the upper and lower portions of the light
beam. Since the components perpendicular to the
polarization direction of the incident beam form two
10   spots on the imaging plane, a finally obtained spot is
an enlarged spot superposed on the spot formed by the
polarized light components parallel to the polarization
direction of the incident beam.

When the polarization directions of light beams in
15   light emitting portions are strictly perpendicular to
each other, the spot of each light emitting portion is
enlarged even during deflection and scanning. This is
because the directions of two principal axes are always
perpendicular to each other. For this reason, the
20   above description can be applied when what has been
handled as a polarization angle difference is handled
as a shift angle from a parallel or orthogonal state.
When the polarization direction is shifted from a
horizontal or vertical state, the state of a spot
25   changes for each light emitting portion. For this
reason, a printing state as shown in, e.g., Fig. 26B is
obtained, resulting in degradation in printing quality.

To measure the direction of a principal axis, a light source for emitting linearly polarized light and a polarizer are used. A polarizing plate is irradiated with light having linear polarization, and the

5   polarizing plate or light source is rotated and adjusted such that the amount of light emerging from the polarizing plate is maximized. Next, a sample whose principal axis direction is to be measured is placed between the light source and the polarizing

10   plate and rotated about the optical axis to detect an angle at which the light amount is maximized. The angle obtained at this time indicates the direction of the principal axis. Alternatively, an angle relationship with which the light amount is minimized

15   may be set between the light source and the polarizing plate, and after insertion of a sample, an angle at which the light amount is minimized may be detected.

<First Embodiment>

Fig. 1 is a sectional view (main-scanning

20   sectional view) showing the main part in the main scanning direction of an optical scanning apparatus according to the first embodiment of the present invention. Fig. 2 is a sectional view (sub-scanning sectional view) showing the main part of the light

25   source means shown in Fig. 1.

In this specification, a direction in which a light beam is reflected and deflected (deflected and

scanned) by deflection means is defined as the main
scanning direction, and a direction perpendicular to
the optical axis of the scanning optical means and the
main scanning direction is defined as the sub scanning

5 direction.

Referring to Fig. 1, light source means 1
comprises, e.g., a monolithic multi-beam semiconductor
laser and has two, first and second light emitting
portions 1a and 1b. The first and second light

10 emitting portions 1a and 1b are separated by a
predetermined distance in the main scanning and sub
scanning directions, as shown in Fig. 2. A collimator
lens 2 converts two divergent light beams emitted from
the light source means 1 into almost parallel light

15 beams. A cylindrical lens (cylinder lens) 4 has a
predetermined refracting power only in the sub scanning
direction so that the substantially parallel light
beams transmitted through the collimator lens 2 are
imaged as substantially linear images on a deflecting

20 surface 5a of an optical deflector 5 (to be described
later) in the sub-scanning section. An aperture stop 3
shapes the light beams emerging from the cylindrical
lens 4 into a desired optimum beam shape. In this
embodiment, the aperture stop 3 is arranged near the

25 deflecting surface 5a of the optical deflector 5 (to be
described later) to reduce a deviation in printing
position of each light beam in the main scanning

direction.

Each of the collimator lens 2, cylindrical lens 4, and aperture stop 3 constitutes an element of incident optical means 8.

5   The optical deflector 5 serving as a deflection means comprises, e.g., a polygon mirror (rotary polyhedral mirror). The optical deflector 5 is rotated in a direction indicated by an arrow A in Fig. 1 at a predetermined speed by drive means (not shown) such as

10   a motor.

A scanning optical means (f-θ lens system) 6 having an f-θ characteristic has two, first and second optical elements (toric lenses) 6a and 6b made of a resin (plastic) molded by the injection molding and

15   forms images of two light beams based on image information deflected by the optical deflector 5 on a photosensitive drum surface 7. The scanning optical means has a correction function for correcting a surface inclination of the optical deflector 5 by

20   making the deflecting surface 5a of the optical deflector 5 and the photosensitive drum surface 7 optically conjugate each other in the sub-scanning section.

The photosensitive drum surface 7 serves as a

25   surface to be scanned (scanning surface).

In this embodiment, the two divergent light beams emitted from the monolithic multi-beam semiconductor

laser 1 are converted into substantially parallel light

beams by the collimator lens 2 and become incident on

the cylindrical lens 4. In the main-scanning section,

the two substantially parallel light beams incident on

5   the cylindrical lens 4 emerge while being kept

unchanged and pass through the aperture stop 3 (the

light beams are partially shielded). In the

sub-scanning section, the light beams converge and pass

through the aperture stop 3 (the light beams are

10   partially shielded) and form substantially linear

images (linear images long in the main scanning

direction) on the deflecting surface 5a of the optical

deflector 5. The two light beams deflected by the

deflecting surface 5a of the optical deflector 5 are

15   guided onto the photosensitive drum surface 7 through

the first and second optical elements 6a and 6b to

optically scan the photosensitive drum surface 7 in a

direction indicated by an arrow B as the optical

deflector 5 is rotated in the direction of an arrow A.

20   With this operation, an image is recorded on the

photosensitive drum surface 7 serving as a recording

medium.

    In this embodiment, the sub-scanning magnification

of the scanning optical means 6 is set to be almost

25   uniform for the entire scanning range such that the

sub-scanning interval between scanning lines becomes

almost constant in an ideal situation.

In this embodiment, the two divergent light beams emitted from the multi-beam semiconductor laser 1 are converted into substantially parallel light beams by the collimator lens 2. The effect of the present

5 invention to be described below can also be obtained even when the light beams are converted into convergent light beams or divergent light beams.

In this embodiment, to facilitate manufacturing and reduce cost, the first and second optical elements

10 6a and 6b of the scanning optical means 6 are molded using a resin material "ZEONEX". For this reason, a principal axis distribution as shown in Figs. 18, 19A, and 19B is present in each of the first and second optical elements 6a and 6b. Hence, as described in the

15 foregoing, if light beams emerging from the first and second light emitting portions 1a and 1b have different polarization angles, the interval between scanning lines in the sub scanning direction is not constant, resulting in degradation in printing quality.

20 According to an experiment and examination by the present inventor, the relationship between the difference in polarization angle between the light beams emitted from the plurality of light emitting portions and the interval error between scanning lines

25 in the sub scanning direction represented that the interval error between scanning lines on the scanning surface was about ±2.5 µm when the angle difference was

30°. Another experiment also revealed that an interval error of 1/5 or more the interval between original scanning lines considerably degraded the printing quality.

5   The sub-scanning resolution of the apparatus of this embodiment is about 1,200 dpi. Hence, an ideal interval between scanning lines is about 21 μm. The interval error is preferably at least 1/5 the interval between original scanning lines, i.e., ±4.2 μm or less.

10   For this purpose, in this embodiment, the polarization angle difference between the light beams emitted from the first and second light emitting portions 1a and 1b is set to be 45° or less in consideration of an interval error originally included

15   in the design value and the decentration of an optical element such that the interval error between scanning lines in the sub scanning direction becomes 1/5 or less the desired interval between the scanning lines. With this arrangement, a multi-beam scanning optical

20   apparatus which reduces the interval error between the scanning lines in the sub scanning direction and can perform high-quality high-speed printing at a relatively low cost is obtained.

In this embodiment, the polarization angle

25   difference between the light beams emitted from the plurality of light emitting portions are set to be 45° or less. This angle difference is preferably 20° or

less.

A lens molded using a resin material has
birefringence, and the directions of principal axes of
birefringence change depending on the position.
5   Especially, an asymmetrical principal axis distribution
is formed in the sub scanning direction, as shown in
Figs. 19A and 19B.

However, when a height (sub-scanning width) h of
the resin lens is as large as 15 times or more of a
10   sub-scanning width t of a light beam passing through
the lens, the asymmetrical distribution of the
principal axes of birefringence in the light beam
becomes relatively small. To reduce the influence of
birefringence, a lens having the above structure is
15   preferably used. In fact, it is difficult for a lens
used for a scanning optical means to satisfy $h/t > 15$
because the cost may increase due to the material cost
and longer molding time.

However, even when use of a lens that satisfies
20   $h/t \leq 15$ makes the problem pointed out in this
specification conspicuous, that problem can be solved
by using the means described in this specification.

In this embodiment, for the deflection-means-side
lens 6a used in the scanning optical means, $h/t = 22.3$,
25   i.e., the lens shape is preferable to reduce the
influence of birefringence. However, for the lens 6b
on the photosensitive drum surface 7 side, $h/t = 11.7$.

That is, the lens is readily affected by birefringence.
However, the influence is reduced using the measures
described above.

When the height (sub-scanning width) h of the
5   scanning lens made of a resin is 1.8 times or more of a
thickness (optical-axis-direction width) d of the
optical element, heat dissipation occurs from the
direction of thickness more than from direction of
height in cooling of the molding process, and
10   consequently, the lens is rapidly cooled and hardened.
For this reason, the directions of principal axes of
birefringence are fixed before the principal axes start
largely tilting. Hence, the asymmetrical distribution
of the principal axes in the sub scanning direction
15   becomes small.

To reduce the influence of birefringence, a lens
having the above structure is preferably used. In
fact, if the thickness is too small, the resin cannot
be smoothly supplied into the mold, resulting in
20   occurrernce of birefringence. In addition, if the
height (sub-scanning width) h of the lens is too large,
the cost undesirably increases.

However, even when use of a lens that satisfies
h/d ≤ 1.8 makes the problem pointed out in this
25   specification conspicuous, that problem can be solved
by using the means described in this specification. In
this embodiment, h/d = 1.53 for the

deflection-means-side lens 6a used in the scanning

optical means, and h/d = 1.63 for the lens 6b on the

photosensitive drum surface 7 side, i.e., the lens

shapes are readily affected by birefringence. However,

5   the influence is reduced using the measures described

above.

The reason why the influence of birefringence

becomes serious when all lenses used for the scanning

optical means are resin lenses having birefringence

10   will be described below.

When the scanning optical means consists of a

plurality of resin lenses having birefringence, the

interval error due to the birefringence almost appears

as an accumulation of influence of birefringence of

15   each lens. This is due to the following reason. Since

the distribution of tilts of principal axes of

birefringence easily depends on the outer shape of a

lens, and each lens used in the scanning optical means

often has a rectangular shape because of the space, the

20   directions of the tilts of the principal axes of

birefringence at a position in the lens are the same

for any lens more or less.

The influence of birefringence also depends on the

direction of incidence of a light beam or the shape of

25   a lens. For this reason, the interval error between

scanning lines in the sub scanning direction does not

strictly linearly change with respect to the main

scanning direction. Hence, when a plurality of lenses having birefringence are used, a portion at which the interval error between scanning lines is locally increased by totaling positions with large interval errors may be formed. If such a portion is locally formed, that portion becomes very noticeable on a printed image, resulting in degradation in printing quality.

The influence of birefringence also depends on the thickness of a lens. Generally, as the thickness increases, the influence of birefringence more readily appears. Hence, even a single but thick resin lens having birefringence readily generates an interval error between scanning lines. Furthermore, when only a single lens is used for the scanning optical means, the lens tends to be thick to obtain an f-θ characteristic and the like. For this reason, if the single lens used for the scanning optical means is a resin lens having birefringence, the interval error between scanning lines is readily generated.

As described above, when all lenses used for the scanning optical means are resin lenses having birefringence, the influence of birefringence is large, and therefore, the interval error between scanning lines readily occurs. However, such a structure is often positively employed to make the cost consistent with the optical performance, though it would be proper

to avoid such a structure. The effect of the present

invention can be obtained especially in this case, and

the degradation in printed image quality due to the

interval error between scanning lines can be reduced by

5   using the measures proposed in the present invention.

In this embodiment, both the two lenses of the

scanning optical means are made of resin lenses having

birefringence. However, the influence is reduced by

using the measures described above.

10   <Second Embodiment>

Fig. 3 is a sectional view (main-scanning

sectional view) showing the main part in the main

scanning direction in the second embodiment of the

present invention. The same reference numerals as in

15   Fig. 1 denote the same elements in Fig. 3.

The second embodiment is different from the

above-described first embodiment in that, e.g., a

polarizing plate 18 serving as a polarized light

limiting means having a function of transmitting only a

20   component in a specific polarization direction is

arranged after an aperture stop 3 arranged rotatably

about the optical axis. The remaining components and

optical function are almost the same as in the first

embodiment whereby the same effect as in the first

25   embodiment is obtained.

That is, the polarized light limiting means 18

consists of, e.g., a polarizing plate having a function

of transmitting only a light beam with a component in a specific polarization direction. The polarizing plate is inserted immediately after the aperture stop 3 while being tilted with respect to the optical axis of the

5   incident optical means 8. The polarizing plate is tilted with respect to the optical axis to reduce return light toward a light source means 1.

In this embodiment, even when two light beams emitted from first and second light emitting portions

10   1a and 1b do not have the same polarization direction, the light beams are transmitted through the polarizing plate 18, thereby obtaining a substantially same polarization direction P before the light beams become incident on first and second optical elements 6a and 6b

15   molded using a resin material. With this arrangement, the interval error between scanning lines in the sub scanning direction is set to be 1/5 or less of the interval between original scanning lines.

In this embodiment, the polarized light limiting

20   means can be adjustably rotated about the optical axis. If the means cannot be adjusted, or if possible, the adjustable angle is too small, the following problem may occur. In the above case, if the polarization angle difference between the light beams emitted from

25   the first and second light emitting portions 1a and 1b is too large, the amounts of light beams emerging from the polarizing plate 18 may have a large difference.

At this time, even though the interval error in the sub

scanning direction can be reduced, the density

undesirably changes for each scanning line, resulting

in degradation in printing quality. Hence, the

5   polarized light limiting means is preferably adjustably

rotated about the optical axis. If such a structure is

impossible, the polarization angle difference between

the light beams emitted from the first and second light

emitting portions 1a and 1b is preferably set to be 45°

10   or less, as in the above-described first embodiment.

Otherwise, the light amounts of the light emitting

portions may be respectively adjusted.

In this embodiment, especially, to effectively

reduce return light toward the light source means 1,

15   the polarizing plate 18 is arranged immediately after

the aperture stop 3. The position of the polarizing

plate 18 is not limited to the above position, and the

same effect as described above can be obtained when the

polarizing plate 18 is set in the optical path between

20   the light source means 1 and a scanning optical means

6.

<Third Embodiment>

Fig. 4 is a sectional view (main-scanning

sectional view) showing the main part in the main

25   scanning direction in the third embodiment of the

present invention. Fig. 5 is a schematic view showing

the main part near a light source means shown in

Fig. 4.   The same reference numerals as in Fig. 1

denote the same elements in Figs. 4 and 5.

The third embodiment is different from the

above-described first embodiment in that first and

5   second light emitting portions 1a and 1b are

independently arranged, and the polarization angles of

light beams emitted from the first and second light

emitting portions 1a and 1b can be adjustably rotated

about the principal axis of a scanning optical means 6.

10   The remaining components and optical function are

almost the same as in the first embodiment whereby the

same effect as in the first embodiment is obtained.

Referring to Fig. 5, light source means 11 has the

first and second light emitting portions 1a and 1b that

15   are independently arranged.   In this embodiment, the

polarization angles of light beams emitted from the

first and second light emitting portions 1a and 1b can

be adjustably rotated about the principal axis of the

scanning optical means 6, thereby reducing the interval

20   error between scanning lines in the sub scanning

direction.   Optical path combining means 9 guides the

optical paths of the light beams emitted from the first

and second light emitting portions 1a and 1b with small

angles in the sub scanning direction such that a

25   desired interval can be finally obtained on the

scanning surface.

In this embodiment, the optical paths of light

beams emitted from the first and second light emitting

portions 1a and 1b are guided in almost the same

direction using the optical path combining means 9, as

shown in Fig. 5. However, when the sub-scanning

5   distance between the first and second light emitting

portions 1a and 1b is sufficiently short, the optical

path combining means 9 may be omitted.

In actual adjustment, for example, a polarizing

plate which passes only a component having a

10   polarization angle substantially perpendicular to a

principal axis that should match a polarization

direction P of an incident beam on the main-scanning

section of first and second optical elements 6a and 6b

is prepared. One of the first light emitting portion

15   1a and second light emitting portion 1b is caused to

emit light, and then, the spot is observed through the

polarizing plate. Since the light component observed

at this time is a polarized light component in a

direction different from the principal axis which

20   should match the polarization direction, the

polarization angle of light beam at the light emitting

portion that is emitting light is adjusted such that

the light amount is minimized. If such light amount

that affects the scanning line interval remains, the

25   polarization angle of the light beam from the light

emitting portion that is emitting light is adjusted

such that two spots formed have almost the same light

amount in the sub scanning direction.

After that, the polarization angle of the light beam emitted from the other light emitting portion is adjusted in the same way as described above. Then, even when the light source means 11 is rotated about the optical axis to adjust the scanning line interval in the sub scanning direction, the scanning line interval does not increase or decrease in accordance with the scanning position because the differences between the principal axes of the first and second optical elements 6a and 6b of the scanning optical means 6 on the main-scanning section and the polarization angles of the first and second light emitting portions 1a and 1b are almost constant. The polarization angles of the light beams emitted from the first and second light emitting portions 1a and 1b may be shifted by the same angle with respect to the principal axes of the first and second optical elements 6a and 6b in consideration of adjustment or the like.

The polarization directions P of the light beams emitted from the light emitting portions may be adjusted by observing the peak light amounts of spots without using any polarizing plate. This is because extraordinary light is minimized when the peak light amount of a spot is maximized, and at this time, the extraordinary light distribution generally becomes almost symmetrical with respect to the main-scanning

section. If the polarization direction P cannot be adjusted due to some reason, the polarization angle difference may be adjusted using a polarizing plate, as described in the second embodiment.

5   In this embodiment, the number of light emitting portions is two. Even when the number of light emitting portions is increased to three or more, as shown in Fig. 6, the same effect as described above can be obtained using the above-described arrangement and

10   adjustment. Referring to Fig. 6, light source means 12 has four light emitting portions 1a to 1d independently provided. Optical path combining means 9a to 9c are the same as in Fig. 5. In this embodiment, the optical path combining means 9 is inserted between the light

15   source means 1 and a collimator lens 2. However, the order of the collimator lens 2 and optical path combining means 9 may be reversed. In this case, a collimator lens must be provided for each light emitting portion.

20   <Fourth Embodiment>

Fig. 7 is a sectional view (main-scanning sectional view) showing the main part in the main scanning direction in the fourth embodiment of the present invention. Fig. 8 is a schematic view showing

25   the main part near light source means shown in Fig. 7. The same reference numerals as in Figs. 4 and 5 denote the same elements in Figs. 7 and 8.

The fourth embodiment is different from the
above-described first embodiment in that light source
means 31 consists of two, first and second monolithic
multi-beam light sources (multi-beam array lasers) 21
5   and 22, and the polarization angles of light beams
emitted from the first and second multi-beam light
sources can be adjustably rotated about the principal
axis of scanning optical means 6. The remaining
components and optical function are almost the same as
10   in the first embodiment whereby the same effect as in
the first embodiment is obtained.

Referring to Figs. 7 and 8, the light source means
31 has the two, first and second monolithic multi-beam
light sources 21 and 22. The first multi-beam light
15   source 21 has two, first and second light emitting
portions 21a and 21b. The second multi-beam light
source 22 has two, first and second light emitting
portions 22a and 22b. An optical path combining means
9 has the same function as shown in Fig. 5, i.e.,
20   guides the optical paths of light beams emitted from
the first and second multi-beam light sources 21 and 22
in substantially the same direction.

In this embodiment, the number of light emitting
portions is increased as compared to the first
25   embodiment, thereby enabling faster and more precise
operation. In addition, the first and second
multi-beam light sources 21 and 22 are independent and

can be adjustably rotated about the principal axis of
the scanning optical means 6. With this arrangement,
the interval error between scanning lines in the sub
scanning direction is reduced.

5   The adjustment method is the same as in the third
embodiment. However, appropriate balancing is
necessary because the polarization angle differences
between the first and second light emitting portions
21a and 21b of the first multi-beam light source 21 and

10   between the first and second light emitting portions
22a and 22b of the second multi-beam light source 22
cannot be changed. If the polarization angle
difference is too large, the polarization angle
difference may be decreased using polarized light

15   limiting means (polarizing plate), as described in the
second embodiment. These effects can be obtained
independently of the number of light sources and the
number of light emitting portions.

<Fifth Embodiment>

20   Fig. 9 is a sectional view (main-scanning
sectional view) showing the main part in the main
scanning direction in the fifth embodiment of the
present invention. The same reference numerals as in
Fig. 1 denote the same elements in Fig. 9.

25   The fifth embodiment is different from the
above-described first embodiment in that a first
optical element 6a of scanning optical means is

decentered in the sub scanning direction. The

remaining components and optical function are almost

the same as in the first embodiment whereby the same

effect as in the first embodiment is obtained.

5   That is, in this embodiment, the first optical

element 6a of the scanning optical means 6 is

decentered in the sub scanning direction, thereby

reducing the interval error between scanning line in

the sub scanning direction.

10   Generally, it is difficult to completely eliminate

the interval difference (distance difference) between a

plurality of light emitting portions in the main

scanning direction without using a relay optical system

or the like. A plurality of light emitting portions

15 have an interval error to some degree in the main

scanning direction. For this reason, even when the

modulation timing for the plurality of light emitting

portions is adjusted to print at the same position in

the main scanning direction, the plurality of light

20 beams from the plurality of light emitting portions

pass through different positions on the first and

second optical elements 6a and 6b of the scanning

optical means 6, as shown in Fig. 10.

For this reason, when a part or all of the optical

25 elements of the scanning optical means 6 are

decentered, the image positions of the light beams

mainly shift in the sub scanning direction in

accordance with the sub-scanning powers at the light

beam passing positions and the optical path length from

the refracting surface to the scanning surface. For

example, assume that the decentered optical element has

5   such optical power in the sub-scanning direction that

becomes larger as being farther from the optical axis,

and the element is decentered to the upper side in

Fig. 11. In this case, when the preceding light beam

forms a scanning line on the upper side as shown in

10   Fig. 11, the light beam that starts scanning next is

bent upward than the preceding light beam, so the

scanning line interval decreases at the scanning start

position, as shown in Fig. 12. Conversely, at the

scanning end position, since the preceding light beam

15   is bent upward than the succeeding light beam, the

scanning line interval increases.

When the power in the sub scanning direction

becomes smaller as being farther from the optical axis,

the above relationship is reversed. The relationship

20   is also reversed when the light beam that scans on the

upper side is not the preceding light beam but the

succeeding light beam.

Even when the power in the sub scanning direction

does not change, the optical path length changes.

25   Hence, the interval between scanning lines is changed

by decentering the optical element in the sub scanning

direction. In this embodiment, the interval error

between scanning lines in the presence of a polarization angle difference is canceled by positively using the above phenomenon.

In this embodiment, the first optical element 6a

5   is decentered. However, even when the second optical element 6b is decentered, as shown in Fig. 13, the same effect as described above can be obtained. Even when both the first and second optical elements 6a and 6b are decentered in balance, as shown in Fig. 14, the

10   same effect as described above can be obtained. In this embodiment, shift decentration perpendicular to the sub scanning direction is employed. However, the same effect as described above can be obtained even when the optical element is tilted in the vertical

15   direction (rotary decentration) about the main scanning axis.

In the present invention, the same effect as described above can be obtained even when both shift decentration and rotary decentration are done.

20   This embodiment may be combined with any one of the above-described first to fourth embodiments.

In the first to fifth embodiments, the number of resin lenses of the present invention in each of which the directions of the principal axes of birefringence

25   change between the lens left end (off-axis) and the lens right end (off-axis) in the main scanning direction (Figs. 17, 18, 19A and 19B), and in each of

which the directions of the principal axes of

birefringence at each lens end form an asymmetrical

distribution in the sub scanning direction (Figs. 19A

and 19B) is two. However, the number of lenses may be

5   one or three or more. Fig. 35 shows an example using a

single resin lens. A refractive optical element (lens)

60 has birefringence and is formed by molding using a

resin.

Further, the scanning optical means 6 may include

10   a reflecting optical element made of glass and having a

power in addition to the refractive optical element

(lens) of the present invention, which has

birefringence and is formed by molding using a resin.

The scanning optical element may include a

15   diffraction surface. The scanning optical element of

the present invention may be either an element having a

diffraction surface formed on a surface of a refractive

optical element (lens) having a power or an element

having a diffraction surface formed on a flat glass

20   surface.

The resin scanning optical element (lens) of the

present invention, which exhibits index anisotropy, may

be either an element having a positive power or an

element having a negative power. In the present

25   invention, the light beam from the light source means 1

may be directly guided to the optical deflector 5

through the aperture stop 3 without using the

collimator lens 2 and the cylindrical lens 4.

As described above, in the first to fifth embodiments, all lenses of the scanning optical means 6 are scanning lenses made of a resin. However, the present invention is not limited to this structure. The scanning optical means 6 may include one or a plurality of scanning lenses made of glass.

<Sixth Embodiment>

Fig. 36 is a sectional view (main-scanning sectional view) showing the main part in the main scanning direction of an optical scanning apparatus according to the sixth embodiment of the present invention.

In this specification, a direction in which a light beam is reflected and deflected (deflected and scanned) by the deflection means is defined as the main scanning direction, and a direction perpendicular to the optical axis of the scanning optical means and the main scanning direction is defined as the sub scanning direction.

Referring to Fig. 36, light source means 10 consists of, e.g., a single-beam semiconductor laser and has one light emitting portion. A collimator lens 2 converts a divergent light beam emitted from the light source means 10 into a substantially parallel light beam. A cylindrical lens (cylinder lens) 4 has a predetermined refracting power only in the sub scanning

direction to focus the substantially parallel light

beam transmitted through the collimator lens 2 as an

almost linear image on a deflecting surface 5a of an

optical deflector 5 (to be described later) in the

5   sub-scanning section. An aperture stop 3 shapes the

light beam emerging from the cylindrical lens 4 into a

desired optimum beam shape. In this embodiment, the

aperture stop 3 is arranged near the deflecting surface

5a of the optical deflector 5 (to be described later)

10   to reduce the shift in printing position of the light

beam in the main scanning direction.

Each of the collimator lens 2, cylindrical lens 4,

and aperture stop 3 constitutes an element of incident

optical means 8.

15   The optical deflector 5 serving as the deflection

means comprises, e.g., a polygon mirror (rotary

polyhedral mirror). The optical deflector 5 is rotated

in a direction indicated by an arrow A in Fig. 36 at a

predetermined speed by drive means (not shown) such as

20   a motor.

A scanning optical means (f-θ lens system) 6

having an f-θ characteristic has two, first and second

optical elements (toric lenses) 6a and 6b made of a

resin (plastic) and forms images of two light beams

25   based on image information deflected by the optical

deflector 5 on a photosensitive drum surface 7. The

scanning optical means has a correction function for

correcting a surface inclination of the optical

deflector 5 by making the deflecting surface 5a of the

optical deflector 5 and the photosensitive drum surface

7 optically conjugate each other in the sub-scanning

5   section.

       The photosensitive drum surface 7 serves as a

surface to be scanned (scanning surface).

       In this embodiment, a divergent light beam emitted

from the single-beam semiconductor laser 10 is

10   converted into a substantially parallel light beam by

the collimator lens 2 and becomes incident on the

cylindrical lens 4. In the main-scanning section, the

single substantially parallel light beam incident on

the cylindrical lens 4 emerges while being kept

15   unchanged and passes through the aperture stop 3 (the

light beam is partially shielded). In the sub-scanning

section, the light beam converges and passes through

the aperture stop 3 (the light beam is partially

shielded) and form a substantially linear image (linear

20   image long in the main scanning direction) on the

deflecting surface 5a of the optical deflector 5. The

single light beam deflected by the deflecting surface

5a of the optical deflector 5 is guided onto the

photosensitive drum surface 7 through the first and

25   second optical elements 6a and 6b to optically scan the

photosensitive drum surface 7 in a direction indicated

by an arrow B as the optical deflector 5 is rotated in

the direction of an arrow A. With this operation, an image is recorded on the photosensitive drum surface 7 serving as a recording medium.

In this embodiment, the sub-scanning magnification
5 of the scanning optical means 6 is set to be almost uniform for the entire scanning range such that the sub-scanning interval between scanning lines becomes almost constant in an ideal situation.

In this embodiment, the single divergent light
10 beam emitted from the single-beam semiconductor laser 10 is converted into a substantially parallel light beam by the collimator lens 2. The effect of the present invention to be described below can also be obtained even when the light beam is converted into a
15 convergent light beam or a divergent light beam.

In this embodiment, to facilitate manufacturing and reduce cost, the first and second optical elements 6a and 6b of the scanning optical means 6 are molded using a resin material "ZEONEX". For this reason, a
20 principal axis distribution as shown in Figs. 18, 19A, and 19B is present in each of the first and second optical elements 6a and 6b. Hence, as described in the foregoing, if light beams emerging from the first and second light emitting portions 1a and 1b have different
25 polarization angles, the interval between scanning lines in the sub scanning direction is not constant, resulting in degradation in printing quality.

According to an experiment by the present
inventor, as shown in Fig. 26A when a sub-scanning
interval error of 1 mm or more was generated between
the left end and the right end of the effective

5   scanning region of scanning lines that run in the main
scanning direction, the printing quality considerably
degraded.

In this embodiment, the polarization angle of the
light beam emitted from the light emitting portion of

10   the light source means 10 is adjusted by rotation about
the optical axis such that the sub-scanning interval
error between the left end and the right end of the
effective scanning region of scanning lines that run in
the main scanning direction becomes less than 1 mm.

15   With this arrangement, a single-beam scanning optical
apparatus which reduces the sub-scanning interval error
between the left end and the right end of the effective
scanning region of scanning lines and can perform
high-quality high-speed printing at a relatively low

20   cost is obtained.

The same effect as described above can also be
obtained by decentering the first optical element 6a of
the scanning optical means in the sub scanning
direction, as in the above-described fifth embodiment.

25   The first optical element 6a is decentered.
However, even when the second optical element 6b is
decentered, as shown in Fig. 13, the same effect as

described above can be obtained. Even when both the

first and second optical elements 6a and 6b are

decentered in balance, as shown in Fig. 14, the same

effect as described above can be obtained. In this

5   embodiment, shift decentration perpendicular to the sub

scanning direction is employed. However, the same

effect as described above can be obtained even when the

optical element is tilted in the vertical direction

(rotary decentration) about the main scanning axis.

10   In the present invention, the same effect as

described above can be obtained even when both shift

decentration and rotary decentration are done.

A lens molded using a resin material has

birefringence, and the directions of principal axes of

15   birefringence change depending on position.

Especially, an asymmetrical principal axis distribution

is formed in the sub scanning direction, as shown in

Figs. 19A and 19B.

However, when a height (sub-scanning width) h of

20   the resin lens is as large as 15 times or more of a

sub-scanning width t of a light beam passing through

the lens, the asymmetrical distribution of the

principal axes of birefringence in the light beam

becomes relatively small. To reduce the influence of

25   birefringence, a lens having the above structure is

preferably used. In fact, it is difficult for a lens

used for a scanning optical means to satisfy $h/t > 15$

because the cost may increase due to the material cost and longer molding time.

However, even when use of a lens that satisfies h/t ≤ 15 makes the problem pointed out in this
5   specification conspicuous, that problem can be solved by using the means described in this specification.

In this embodiment, for the deflection-means-side lens 6a used in the scanning optical means, h/t = 22.3, i.e., the lens shape is preferable to reduce the
10   influence of birefringence. However, for the lens 6b on the photosensitive drum surface 7 side, h/t = 11.7. That is, the lens is readily affected by birefringence. However, the influence is reduced using the measures described above.

15   When the height (sub-scanning width) h of the scanning lens made of a resin is 1.8 times or more of a thickness (optical-axis-direction width) d of the optical element, heat dissipation occurs from the direction of thickness more than from direction of
20   height in cooling of the molding process, and consequently, the lens is rapidly cooled and hardened. For this reason, the directions of principal axes of birefringence are fixed before the principal axes start largely tilting. Hence, the asymmetrical distribution
25   of the principal axes in the sub scanning direction becomes small.

To reduce the influence of birefringence, a lens

having the above structure is preferably used. In

fact, if the thickness is too small, the resin cannot

be smoothly supplied into the mold, resulting in

birefringence. In addition, if the height

5   (sub-scanning width) h of the lens is too large, the

cost undesirably increases.

However, even when use of a lens that satisfies

h/d ≤ 1.8 makes the problem pointed out in this

specification conspicuous, that problem can be solved

10   by using the means described in this specification. In

this embodiment, h/d = 1.53 for the

deflection-means-side lens 6a used in the scanning

optical means, and h/d = 1.63 for the lens 6b on the

photosensitive drum surface 7 side, i.e., the lens

15   shapes are readily affected by birefringence. However,

the influence is reduced using the measures described

above.

If there are a plurality of scanning lenses made

of a resin, the interval error between scanning lines

20   due to birefringence appears as an accumulation of

influence of birefringence of each lens.

However, to make the cost consistent with the

optical performance, a plurality of (two or more)

scanning lenses made of a resin need often be used.

25   The influence of birefringence also depends on the

direction of incidence of a light beam or the shape of

a lens. For this reason, the interval error between

scanning lines in the sub scanning direction does not linearly change with respect to the main scanning direction. When a plurality of lenses are present, the error may be canceled at a certain portion and amplified at another portion. If such a portion is locally formed, that portion becomes very noticeable, resulting in degradation in printing quality. In this embodiment, two lenses having birefringence are used for the scanning optical means. However, the influence is reduced using the measures described above.

The reason why the influence of birefringence becomes serious when all lenses used for the scanning optical means are resin lenses having birefringence will be described below.

When the scanning optical means consists of a plurality of resin lenses having birefringence, the interval error due to the birefringence almost appears as an accumulation of influence of birefringence of each lens. This is due to the following reason. Since the distribution of tilts of principal axes of birefringence easily depends on the outer shape of a lens, and each lens used in the scanning optical means often has a rectangular shape because of the space, the directions of the tilts of the principal axes of birefringence at a position in the lens are the same for any lens more or less.

The influence of birefringence also depends on the

direction of incidence of a light beam or the shape of a lens. For this reason, the interval error between scanning lines in the sub scanning direction does not strictly linearly change with respect to the main

5 scanning direction. Hence, when a plurality of lenses having birefringence are used, influences from portions contributing to occurrence of large interval error are accumulated to thereby cause a portion at which the interval error between scanning lines is locally

10 increased. If such a portion is locally formed, that portion becomes very noticeable on a printed image, resulting in degradation in printing quality.

The influence of birefringence also depends on the thickness of a lens. Generally, as the thickness

15 increases, the influence of birefringence more readily appears. Hence, even a single but thick resin lens having birefringence readily generates a sub-scanning interval error between the left end and the right end of the effective scanning region of scanning lines.

20 Furthermore, when only a single lens is used for the scanning optical means, the lens tends to be thick to obtain an f-θ characteristic and the like. For this reason, if the single lens used for the scanning optical means is a resin lens having birefringence, the

25 interval error between scanning lines is readily generated.

As described above, when all lenses used for the

scanning optical means are resin lenses having

birefringence, the influence of birefringence is large,

and therefore, the sub-scanning interval error between

the left end and the right end of the effective

5   scanning region of scanning lines readily occurs.

However, such a structure is often positively employed

to make the cost consistent with the optical

performance, though it would be proper to avoid such a

structure.   The effect of the present invention can be

10   obtained especially in this case, and the degradation

in printed image quality due to the interval error

between scanning lines can be reduced by using the

measured proposed in the present invention.

In this embodiment, both the two lenses of the

15   scanning optical means are made of resin lenses having

birefringence.   However, the influence is reduced by

using the measures described above.

In the sixth embodiment, the number of resin

lenses of the present invention in each of which the

20   directions of the principal axes of birefringence

change between the lens left end (off-axis) and the

lens right end (off-axis) in the main scanning

direction (Figs. 17, 18, 19A and 19B), and each of

which the directions of the principal axes of

25   birefringence at each lens end form an asymmetrical

distribution in the sub scanning direction (Figs. 19A

and 19B) is two.   However, the number of lenses may be

one or three or more.

Further, the scanning optical means 6 may include
a reflecting optical element made of glass and having a
power in addition to the refractive optical element

5   (lens) of the present invention, which has
birefringence and is formed by molding using a resin.

The scanning optical element may include a
diffraction surface. The scanning optical element of
the present invention may be either an element having a

10   diffraction surface formed on a surface of a refractive
optical element (lens) having a power or an element
having a diffraction surface formed on a flat glass
surface.

The resin scanning optical element (lens) of the

15   present invention, which exhibits index anisotropy, may
be either an element having a positive power or an
element having a negative power.

As described above, in the sixth embodiment, all
lenses of the scanning optical means 6 are scanning

20   lenses made of a resin. However, the present invention
is not limited to this structure. The scanning optical
means 6 may include one or a plurality of scanning
lenses made of glass.

<Image Forming Apparatus>

25   Fig. 15 is a sectional view showing the main part
in the sub scanning direction of an image forming
apparatus (electrophotographic printer) according to an

embodiment using the scanning optical apparatus
according to any one of the first to fifth embodiments
of the present invention. Referring to Fig. 15, an
image forming apparatus 104 receives code data Dc from
5   an external device 117 such as a personal computer.
The code data Dc is converted into image data (dot
data) Di by a printer controller 111 in the apparatus.
The image data Di is input to an optical scanning unit
(optical scanning apparatus) 100 according to any one
10   of the first to fifth embodiments of the present
invention. A light beam 103 modulated in accordance
with the image data Di is emitted from the optical
scanning unit 100. The photosensitive surface of a
photosensitive drum 101 is scanned in the main scanning
15   direction by the light beam 103.

The photosensitive drum 101 serving as a static
latent image carrier (photosensitive body) is rotated
clockwise by a motor 115. In accordance with this
rotation, the photosensitive surface of the
20   photosensitive drum 101 moves relative to the light
beam 103 in the sub scanning direction perpendicular to
the main scanning direction. A charging roller 102 for
uniformly charging the surface of the photosensitive
drum 101 is arranged on the upper side of the
25   photosensitive drum 101 and abuts against its surface.
The surface of the photosensitive drum 101, which is
charged by the charging roller 102, is irradiated with

the light beam 103 scanned by the optical scanning unit 100.

As described above, the light beam 103 is modulated on the basis of the image data Di. When the

5 photosensitive drum surface is irradiated with the light beam 103, an electrostatic latent image is formed on the surface of the photosensitive drum 101. This electrostatic latent image is developed as a toner image by a developer 107 which abuts against the

10 photosensitive drum 101 on the downstream side of the irradiation position of the light beam 103 along the rotation direction of the photosensitive drum 101. Toner particles used here have, e.g., charges opposite to those applied by the charging roller 102. A portion

15 (image portion) to which the toner sticks is an unexposed portion of the photosensitive drum. That is, in this embodiment, so-called normal development is performed. In this embodiment, inverted development may be done to make the toner stick to an exposed

20 portion of the photosensitive drum.

The toner image developed by the developer 107 is transferred onto a paper sheet 112 as a transfer member by a transfer roller 108 arranged on the lower side of the photosensitive drum 101 to oppose the

25 photosensitive drum 101. The paper sheet 112 is stored in a paper cassette 109 in front (right side in Fig. 15) of the photosensitive drum 101. Manual feed

is also possible.   A feed roller 110 is arranged at an

end portion of the paper cassette 109 to feed the paper

sheet 112 in the paper cassette 109 to a convey path.

The paper sheet 112 having an unfixed toner image

5   transferred thereon in the above way is conveyed to a

fixing device on the rear side (left side in Fig. 15)

of the photosensitive drum 101.   The fixing device

comprises a fixing roller 113 having a fixing heater

(not shown) inside and a press roller 114 pressed

10   against the fixing roller 113.   The unfixed toner image

on the paper sheet 112 is fixed by pressing the paper

sheet 112 conveyed from the transfer section by the

press portion between the fixing roller 113 and the

press roller 114 and heating the paper sheet 112.

15   Discharge rollers 116 are arranged on the rear side of

the fixing roller 113 to discharge the fixed paper

sheet 112 from the image forming apparatus.

Although not illustrated in Fig. 15, the printer

controller 111 executes not only data conversion

20   described above but also control for the sections in

the image forming apparatus 104, including the motor

115, and a polygon motor and the like in the optical

scanning unit 100.

According to the present invention, there is

25   provided a multi-beam scanning optical apparatus in

which

the scanning optical means has at least one

scanning optical element made of a resin,

in the scanning optical element made of the resin,
with respect to an optical axis in a main scanning
direction, birefringence at one end of the scanning

5   optical element made of the resin has principal axes in
directions different from those of the principal axes
of birefringence at the other end of the scanning
optical element made of the resin due to a stress
distribution formed upon cooling in a molding process,

10   an interval between adjacent scanning lines of
scanning lines formed on the scanning surface by the
plurality of light beams whose images are formed on the
scanning surface through the scanning optical element
made of the resin changes in the main scanning

15   direction in an effective scanning region, and

the apparatus comprises at least one setting means
for setting a sub-scanning interval error between the
scanning lines due to a polarization angle difference
between the light beams emitted from the plurality of

20   light emitting portions to be not more than 1/5 of a
desired scanning line interval, whereby high-quality
high-speed printing can be performed with a relatively
simple arrangement, and an image forming apparatus
using the multi-beam scanning optical apparatus is

25   provided.